



Designation: C179 – 14 (Reapproved 2019)

Standard Test Method for Drying and Firing Linear Change of Refractory Plastic and Ramming Mix Specimens¹

This standard is issued under the fixed designation C179; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the drying shrinkage and of the combined drying and linear change of refractory ramming mixes and plastics.

1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

- C113 Test Method for Reheat Change of Refractory Brick
- C134 Test Methods for Size, Dimensional Measurements, and Bulk Density of Refractory Brick and Insulating Firebrick
- C181 Test Method for Workability Index of Fireclay and High-Alumina Refractory Plastics
- C1054 Practice for Pressing and Drying Refractory Plastic and Ramming Mix Specimens
- E177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods

¹ This test method is under the jurisdiction of ASTM Committee C08 on Refractories and is the direct responsibility of Subcommittee C08.09 on Monolithics.

Current edition approved April 1, 2019. Published April 2019. Originally approved in 1943. Last previous edition approved in 2014 as C179–14. DOI: 10.1520/C0179-14R19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

E691 Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method

3. Significance and Use

3.1 This test method is useful in quantitatively rating or ranking both ramming and refractory plastics by their linear stability after heating.

3.2 This test method is also useful for determining whether a ramming or refractory plastic can be used in a specified application based on linear change criteria.

3.3 This test method excludes basic and carbon-bearing materials.

3.4 This test method can produce data for the engineering and design of refractory installations. The linear change data can be used to determine the number of joints necessary to maintain integrity of ramming or refractory plastic in a large installation.

4. Apparatus

4.1 *Kiln*, electric or gas type, of such design that the flame, as coming directly from the burner, cannot impinge upon the test specimens.

4.2 *Measuring Device*, capable of being read to 0.02 in. (0.5 mm). A hooked rule, 12 in. (305 mm), is convenient to use and a suitable type is described in Test Methods C134. Other measuring devices, such as calipers or dial gages, of the same or better precision may also be used.

5. Test Specimens

5.1 *Number of Specimens*—A minimum of six specimens molded from the sample (see Note 1) of refractory plastic will be required. Half of the specimens shall be used for the test and the other half used as supporting pieces during the kiln heat treatment.

NOTE 1—For pressing and drying the specimens, see Practice C1054.

5.2 *Measurement of Specimens*—Using the measuring device, measure the bar for all dimensions to the nearest 0.02 in. (0.5 mm). Label and make reference marks to indicate the exact length measurement points. Caution should be taken, as deformation of the specimens may be caused by handling.

5.3 *Drying of Specimens*—Dry specimens should be dried as stated in Practice C1054, 6.6.

5.4 *Measuring Dried Specimens*—Measure specimens as stated in 5.2.

6. Procedure

6.1 *Placing Specimens in Kiln*—Place the dried specimens in the kiln in accordance with Test Method C113, with the exception that the supporting brick shall consist of the three refractory plastic brick prepared for that purpose.

6.2 *Temperature Measurements*—Conduct temperature measurements in accordance with Test Method C113.

6.3 *Test Atmosphere*—At all temperatures above 1470 °F (800 °C), operate the kiln so that the atmosphere shall contain a minimum of 0.5 % oxygen with 0 % combustibles.

6.4 *Test Temperature Schedule*—Operate the kiln so as to conform to the appropriate heating schedule for the class of refractory being tested, as specified in Table 1 of Test Method C113.

6.5 *Measuring Fired Specimens*—After completion of the heating schedule, cool the specimens in the closed kiln to under 800 °F (425 °C) before removing to the air. After cooling to room temperature, remeasure them in accordance with 5.2. Record the fired length of each of the three test specimens.

7. Calculation and Report

7.1 *Drying Linear Change*—Calculate the drying linear change as a percentage based on the original length of the specimen as measured in 5.2. Calculate using Eq 1:

$$DLC = ((L_D - L_O)/L_O) \times 100 \tag{1}$$

where:

- DLC = drying linear change, %,
- L_D = dried length, in. (mm), and
- L_O = original length, in. (mm).

A negative value indicates shrinkage, and a positive value growth or expansion of the specimen. Report the average value for the three specimens to the nearest 0.1 %.

7.2 *Combined Linear Change Due to Drying and Firing*—Calculate the combined drying and firing linear change as a percentage based on the original length of the specimen as measured in 5.2. Calculate using Eq 2:

$$FLC = ((L_F - L_O)/L_O) \times 100 \tag{2}$$

where:

- FLC = combined drying and firing linear change, %,
- L_F = fired length, in. (mm), and

L_O = original length, in. (mm).

A negative value indicates shrinkage, and a positive value growth or expansion of the specimen. Report the average value for the three specimens to the nearest 0.1 %.

7.3 The report shall include the following:

7.3.1 Workability of the refractory plastic determined in accordance with Test Method C181.

7.3.2 Firing temperature used or heating schedule from Table 1 of Test Method C113.

8. Precision and Bias

8.1 The precision of this test method is based on an interlaboratory study conducted in 2012. A total of five laboratories participated in this study in an effort to determine the intralaboratory and interlaboratory precision of this test method. Laboratories were asked to report three test results per material, and each test result was defined as a single analytical determination. Practice E691 was followed for the design and analysis of the data, except for the limited number of laboratories submitting results. All details are given in RR:C08-1024.³ Two of the five laboratories had test results higher than the critical *h* and critical *k* values indicating some type of issue occurred, but the subcommittee decided to include these laboratory results anyway due to the limited number of laboratories already involved in the study.

8.1.1 *Repeatability, r*—The difference between repetitive results obtained by the same operator in a given laboratory, applying the same test method with the same apparatus under constant operating conditions on identical test material within short intervals of time would, in the long run, in the normal and correct operation of the test method, exceed the following values only in one case in 20.

8.1.1.1 Repeatability can be interpreted as the maximum difference between two results, obtained under repeatability conditions, that is accepted as plausible due to random causes under normal and correct operation of the test method.

8.1.1.2 Repeatability limits are listed in Tables 1-3.

8.1.2 *Reproducibility, R*—The difference between two single and independent results obtained by different operators applying the same test method in different laboratories, using different apparatus on identical test material would, in the long run, in the normal and correct operation of the test method, exceed the following values only in one case in 20.

8.1.2.1 Reproducibility can be interpreted as the maximum difference between two results, obtained under reproducibility

³ Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:C08-1024. Contact ASTM Customer Service at service@astm.org.

TABLE 1 Linear Change (Green to Dry), %

Material	Average Linear Change, %, ^A Xbar	Repeatability Standard Deviation, <i>sr</i>	Reproducibility Standard Deviation, <i>sR</i>	Repeatability Limit, <i>r</i>	Reproducibility Limit, <i>R</i>
Air Bond (A)	-1.0727	0.0963	0.1235	0.2697	0.3457
Phos Plastic (B)	-0.4573	0.1684	0.3734	0.4716	1.0456
High Workable Phos Plastic (C)	-0.8840	0.0884	0.2546	0.2474	0.7128

^A The average of the laboratories' calculated averages.

TABLE 2 Linear Change (Dry to Fired), %

Material	Average Linear Change, %, ^A \bar{X}	Repeatability Standard Deviation, s_r	Reproducibility Standard Deviation, s_R	Repeatability Limit, r	Reproducibility Limit, R
Air Bond (A)	-0.1867	0.0532	0.2590	0.1490	0.7252
Phos Plastic (B)	-0.0947	0.1473	0.3320	0.4125	0.9296
High Workable Phos Plastic (C)	-0.0600	0.0463	0.2600	0.1295	0.7281

^A The average of the laboratories' calculated averages.

TABLE 3 Linear Change (Green to Fired), %

Material	Average Linear Change, %, ^A \bar{X}	Repeatability Standard Deviation, s_r	Reproducibility Standard Deviation, s_R	Repeatability Limit, r	Reproducibility Limit, R
Air Bond (A)	-1.2593	0.1052	0.2453	0.2945	0.6867
Phos Plastic (B)	-0.5520	0.1020	0.5504	0.2855	1.5410
High Workable Phos Plastic (C)	-0.9440	0.0809	0.0985	0.2264	0.2759

^A The average of the laboratories' calculated averages.

conditions, that is accepted as plausible due to random causes under normal and correct operation of the test method.

8.1.2.2 Reproducibility limits are listed in **Tables 1-3**.

8.1.3 The terms *repeatability limit* and *reproducibility limit* are used as specified in Practice **E177**.

8.1.4 Any judgment in accordance with **8.1.1** and **8.1.2** would normally have an approximate 95 % probability of being correct; however, the precision statistics obtained in this interlaboratory study (ILS) must not be treated as exact mathematical quantities that are applicable to all circumstances and uses. The limited number of laboratories reporting results guarantees that there will be times when differences greater than predicted by the ILS results will arise, sometimes with considerably greater or smaller frequency than the 95 % probability limit would imply. Consider the repeatability limit

and the reproducibility limit as general guides, and the associated probability of 95 % as only a rough indicator of what can be expected.

8.2 *Bias*—There was no accepted reference material at the time of this study suitable for determining the bias for this test method; therefore, no statement on bias can be made.

8.3 This precision statement was determined through statistical examination of 135 results, from a total of five laboratories, on three different materials.

9. Keywords

9.1 linear change; plastic; ramming mix; refractory; shrinkage

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/



Contact ASTM

Call Us

Monday through Friday 8:30am-6:00pm Eastern US
Standard Time

Sales & Support

1-877-909-2786 (USA & Canada)

International

001-610-832-9585 (Customer Service)

001-610-832-9578 (Technical Support)

ASTM Headquarters

100 Barr Harbor Drive
P.O. Box C700
West Conshohocken, PA
19428-2959, USA
Tel: +1.610.832.9500
Fax: +1.610.832.9555
service@astm.org
[Directions](#)

Washington Office

1850 M Street, NW
Suite 1030
Washington, DC 20036
[Jeffrey Grove](#)
Tel: +1.202.223.8505

Latin America Office

EnginZone
Monterosa 233
of. 402 Chacarilla del Estanque
Surco, Lima 33
PERU
[Maria Isabel Barrios](#)
Tel: +51 (1) 205-5502



Contact ASTM

Call Us

Monday through Friday 8:30am-6:00pm Eastern
US Standard Time

Sales & Support

1-877-909-2786 (USA & Canada)

International

001-610-832-9585 (Customer Service)

001-610-832-9578 (Technical Support)

Canada Office

171 Nepean Street, Suite 400
Ottawa, ON K2P 0B4

[Diane Thompson](#)

Tel: +1.613.751.3409

Brussels Office

Rue de la Loi 67
B-1040 Brussels,
Belgium

[Sara Gobbi](#)

Tel +32.(0)2.8405127

China Office

Suite EF-09, Twin Towers East,
B-12 Jianguomenwai Ave.
Chaoyang District, Beijing, P.R. China
100022

[Liu Fei](#)

Tel: +86.10.5109.6033

Fax: +86.10.5109.6039



Contact ASTM

Call Us

Monday through Friday 8:30am-6:00pm Eastern
US Standard Time

Sales & Support

1-877-909-2786 (USA & Canada)

International

001-610-832-9585 (Customer Service)

001-610-832-9578 (Technical Support)

Media Contact

[Nathan Osburn](#), Director,
Corporate Communications
Tel: +610.832.9603