



Designation: D2392 – 15 (Reapproved 2021)

Standard Test Method for Color of Dyed Aviation Gasolines¹

This standard is issued under the fixed designation D2392; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope

1.1 This test method covers the determination of the acceptability of color of dyed aviation gasolines.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use. For specific warning statements, see Annex A1.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Summary of Test Method

2.1 The hue and color intensity of a sample of the gasoline to be tested are compared with those of glass permanent-color standards.

3. Significance and Use

3.1 Aviation gasolines are dyed different colors for easy identification of grade, thus minimizing possibilities for fueling aircraft with fuel of the wrong grade.

4. Apparatus

4.1 *Color Comparator*, split-field, for viewing simultaneously (by transmitted light) the sample to be tested and the combination of the reference liquid and the glass permanent-color standard.

4.2 *Fluid Tubes*, of glass, 200 mm viewing depth, with a fused-on plane bottom plate.

4.3 *Plungers, Fluid Type*, of polished optical glass.

4.4 *Aviation Gasoline Color Standards*,² permanent-color glass disks.

5. Material

5.1 The reference liquid can be either distilled water or a sample of the gasoline to be tested before the addition of dye or lead alkyl fluid. (**Warning**—Gasoline is extremely flammable. See A1.1 and A1.2.)

6. Procedure

6.1 Clean the optical surfaces of the color comparator. Insert the empty fluid tubes in the comparator and adjust the position of the light source until the intensities of the light from both halves of the comparator split-field are equal.

6.2 Rinse and fill one of the tubes with the reference liquid to be used and insert the plunger. Wipe all excess reference liquid from the outside of the tube and from the top of the plunger, and insert the tube on the left side of the comparator.

6.3 Rinse and fill the other tube with the sample to be tested, and insert the plunger. Wipe all excess sample from the outside of the tube and from the top of the plunger, and insert the tube in the right side of the comparator, so that it is directly below the larger of the two openings when the access door is closed.

6.4 Insert the glass permanent-color standards into the comparator and rotate the standards until the color section can be viewed by transmitted light. Turn on the light source and compare the two fields for hue and intensity with the minimum and maximum color sections of the glass permanent-color standards.

6.5 Determine if the hue is approximately the same as the standard and if the intensity of the color is between, or equivalent to, the minimum and maximum, in which case the

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.05 on Properties of Fuels, Petroleum Coke and Carbon Material.

Current edition approved Jan. 1, 2021. Published February 2021. Originally approved in 1965. Last previous edition approved in 2015 as D2392 – 15. DOI: 10.1520/D2392-15R21.

² The sole source of supply of the apparatus known to the committee at this time is Tintometer Ltd, Solar Way, Solstice Park, Salisbury, United Kingdom, SP47SZ. If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee,¹ which you may attend.

color of the sample is acceptable. If the hue is different from the standard or if the intensity lies outside the minimum and maximum color sections, report the test as a fail.

7. Report

7.1 Report the color as Acceptable or Fail.

8. Precision and Bias

8.1 *Precision*—In the case of pass-fail data no generally accepted method for determining precision is currently available.

8.2 *Bias*—No justifiable statement can be made on the bias in this test method for determining the acceptability of the color of dyed aviation gasoline because it is a pass-fail test.

9. Keywords

9.1 aviation gasoline; color; dyed aviation gasoline; gasoline

ANNEX

(Mandatory Information)

A1. WARNING STATEMENTS

A1.1 Gasoline (Containing Lead)

A1.1.1 Keep away from heat, sparks, and open flame.

Keep container closed.

Use with adequate ventilation.

Avoid buildup of vapors and eliminate all sources of ignition, especially nonexplosion-proof electrical apparatus and heaters.

Avoid prolonged breathing of vapor or spray mist.

Avoid prolonged or repeated skin contact.

A1.2 Gasoline (White or Unleaded)

A1.2.1 Keep away from heat, sparks, and open flame.

Keep container closed.

Use with adequate ventilation.

Avoid buildup of vapors and eliminate all sources of ignition, especially nonexplosion-proof electrical apparatus and heaters.

Avoid prolonged breathing of vapor or spray mist.

Avoid prolonged or repeated skin contact.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>