



Designation: D329 – 07 (Reapproved 2021)

Standard Specification for Acetone^{1,2}

This standard is issued under the fixed designation D329; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope

1.1 This specification covers acetone (99.5 % grade).

1.2 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use. Specific hazard statements are given in 1.5 and 4.1.*

1.5 This specification specifies the use of a U.S. Occupational Safety and Health Administration (OSHA)-designated hazardous chemical, acetone. For hazard information and guidance see the supplier’s Material Safety Data Sheet.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*³

¹ This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved July 1, 2021. Published August 2021. Originally approved in 1931. Last previous edition approved in 2013 as D329 – 07 (2013). DOI: 10.1520/D0329-07R21.

² The compound is also known under the names dimethyl ketone and 2-propanone.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material (Withdrawn 2021)⁴

D1078 Test Method for Distillation Range of Volatile Organic Liquids

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D1296 Test Method for Odor of Volatile Solvents and Diluents (Withdrawn 2021)⁴

D1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products

D1363 Test Method for Permanganate Time of Acetone and Methanol

D1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method) (Withdrawn 2021)⁴

D1476 Test Method for Heptane Miscibility of Lacquer Solvents (Withdrawn 2021)⁴

D1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products

D1614 Test Method for Alkalinity in Acetone

D1722 Test Method for Water Miscibility of Water-Soluble Solvents

D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E300 Practice for Sampling Industrial Chemicals

2.2 *U.S. Federal Specification:*

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of⁵

3. Properties

3.1 Acetone (99.5 % grade) shall conform to the following requirements:

⁴ The last approved version of this historical standard is referenced on www.astm.org.

⁵ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, <http://www.dodssp.daps.mil>.

Acidity (free acid as acetic) wt %, max	0.002 (equivalent to 0.019 mg of KOH/g of sample)
Aldehydes	passes test
Alkalinity (as ammonia) wt %, max	0.001
Apparent specific gravity: 20/20 °C	0.7910 to 0.7930 or
25/25 °C	0.7865 to 0.7885
Assay wt %, min	99.5
Color Pt-Co, max (Note 1)	5
Distillation range 760 mmHg (Note 3)	shall distill entirely within a 1.0 °C range which shall include 56.1 °C
Nonvolatile matter mg/100 mL, max	5
Odor (Note 3)	nonresidual
Permanganate time	color of added KMnO ₄ must be retained for at least 30 minutes at 25 °C in the dark
Water wt %, max	0.5 (Note 2)
Water miscibility	passes test

NOTE 1—Instrumental Pt-Co color determined by Test Method D5386 has been shown to have no statistically significant difference from Pt-Co color determined by Test Method D1209. However, it is not known whether acetone was part of the sample set included in the interlaboratory study.

NOTE 2—This quantitative water limit ensures that the material is miscible without turbidity with 19 volumes of 99 % heptane at 20 °C. Test Method D1476 may serve as a useful alternative method to determine the presence of water. Because it is a qualitative test, its use would require agreement between user and supplier.

NOTE 3—Optional: Test only when agreed upon as necessary between the purchaser and the supplier.

4. Sampling

4.1 The material shall be sampled in accordance with Practice E300. **Warning**—Acetone is highly flammable.

5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

5.1.1 *Acidity*—Test Method D1613.

5.1.2 *Aldehydes*—Dilute 2.5 mL of the specimen with water to 10 mL. Prepare a control containing 0.04 mg of formalde-

hyde in 10 mL of water. To both the specimen solution and the control, add 0.15 mL of a 5 % solution of 5,5-dimethyl-1,3-cyclohexanedione in alcohol. Evaporate each on a steam bath until the acetone is volatilized. Dilute each to 10 mL and cool quickly in an ice bath with vigorous stirring. Any turbidity produced in the specimen solution shall be no greater than that produced in the control.

5.1.3 *Alkalinity*—Test Method D1614.

5.1.4 *Apparent Specific Gravity*—Determine the apparent specific gravity by any convenient method that is accurate to the fourth decimal place, the temperature of both specimen and water being 20 °C or 25 °C. See Guide D268 and Test Method D4052.

5.1.5 *Assay*—Assay is determined by difference; 100 % minus (% water + % acidity), assuming that no other impurities are present.

5.1.6 *Color*—Test Method D1209 (see Note 1).

5.1.7 *Distillation Range*—Test Method D1078 using a temperature measuring device having a range of 48 °C to 102 °C and a resolution of 0.1 °C.

5.1.8 *Nonvolatile Matter*—Test Method D1353.

5.1.9 *Odor*—Test Method D1296.

5.1.10 *Permanganate Time*—Test Method D1363.

5.1.11 *Water*—Test Methods D1364.

5.1.12 *Water Miscibility*—Test Method D1722.

6. Packaging and Package Marking

6.1 Package size shall be agreed upon between the purchaser and the supplier.

6.2 Packaging shall conform to applicable carrier rules and regulations or when specified shall conform to Federal Specification PPP-C-2020.

7. Keywords

7.1 acetone; aldehydes test; dimethyl ketone; 2-propanone; solvents

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/