

8. Procedure

8.1 Determine the moisture content of an as-received representative portion of the sample using the xylene extraction Test Method described in D2867. If the as-received sample is wet, drain it of all free liquid before the representative sample is taken.

8.2 Weigh to 0.1 mg accuracy a crucible and cover that have been ignited in a muffle furnace regulated at 950 °C for 30 min and cooled in a desiccator. Record the weight.

8.3 Using a spoon or spatula, dip from the sample bottle approximately 1 g of the as-received sample and place it in the pre-dried and tared crucible. Cover it with a lid and immediately weigh it to the nearest 0.1 mg.

8.4 Place the covered crucible in the muffle furnace regulated at 950 ± 25 °C for 7 min ± 10 s.

8.5 Remove the covered crucible from the muffle furnace and cool to room temperature in a desiccator.

8.6 Weigh the covered crucible to the nearest 0.1 mg. Record the weight.

9. Calculation

9.1 Calculate the weight loss percent as follows:

$$\text{Weight loss, \%} = [(C - D)/(C - B)] \times 100 \quad (1)$$

where:

B = mass of crucible and cover, g,

C = mass of crucible, cover, and sample, g, and

D = mass of crucible, cover, and de-volatilized sample, g.

9.2 Calculate the volatile matter content of the sample as follows:

$$VM, \% = E - F \quad (2)$$

where:

VM = volatile matter content of as-received sample, %,

E = weight loss, % (as defined in 9.1), and

F = moisture, % (as measured in 8.1).

10. Precision and Bias

10.1 An interlaboratory study of this test method was conducted in 1996. Each of seven laboratories tested three randomly drawn specimens from each of three different activated carbons containing volatile matter content. Carbon A was a coconut shell gas phase carbon containing gasoline vapors. Carbon B was a coal-based liquid phase carbon containing organic components from gasoline. Carbon C was a coconut shell vapor phase carbon containing chlorinated organic compounds. The average volatile matter contents were 24.7 %, 9.1 %, and 12.9 %, respectively. In order to determine the volatile matter content of the samples, their moisture contents were determined according to Test Method D2867 and were found to be 3.54 %, 35.2 %, and 3.87 %, respectively. Practice E691 and E691 computer software were used to design the study and analyze the resulting data.

10.2 95 % Limit on Repeatability (Within Laboratory), %:

	Activated Carbon		
	A	B	C
Volatile Matter Content, %	1.38	0.63	0.44

10.3 95 % Limit on Reproducibility (Between Laboratories), %:

	Activated Carbon		
	A	B	C
Volatile Matter Content, %	1.54	1.32	1.47

NOTE 1—The terms “limit on repeatability” and “limit on reproducibility” are used as specified in Practice E177.

11. Keywords

11.1 activated carbon; volatile matter

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/